

92 AG series

x92x38mm



General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Plastic(UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

Model	*Bearing System	Rated Voltage	Operating Voltage Range	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
Part NO.	B / S / F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	g
AGE09238B12L	B	12	7.0~13.2	0.55	4400	2.66	94.11	14.58	0.57	51.2	250
AGE09238B24L	B	24	14.0~26.4	0.30	4400	2.66	94.11	14.58	0.57	51.2	250
AGE09238B48L	B	48	28.0~56.0	0.25	4400	2.66	94.11	14.58	0.57	51.2	250
AGE09238B12M	B	12	7.0~13.2	0.68	4800	2.90	102.55	17.33	0.68	54.1	250
AGE09238B24M	B	24	14.0~26.4	0.33	4800	2.90	102.55	17.33	0.68	54.1	250
AGE09238B48M	B	48	28.0~56.0	0.21	4800	2.90	102.55	17.33	0.68	54.1	250
AGE09238B12H	B	12	7.0~13.2	1.22	6000	3.63	128.13	25.94	1.02	60.5	250
AGE09238B24H	B	24	14.0~26.4	0.68	6000	3.63	128.13	25.94	1.02	60.5	250
AGE09238B48H	B	48	28.0~56.0	0.36	6000	3.63	128.13	25.94	1.02	60.5	250
AGE09238B12U	B	12	7.0~13.2	1.96	7000	4.31	152.32	36.84	1.45	64.4	250
AGE09238B24U	B	24	14.0~26.4	1.02	7000	4.31	152.32	36.84	1.45	64.4	250
AGE09238B48U	B	48	28.0~56.0	0.60	7000	4.31	152.32	36.84	1.45	64.4	250
AGE09238B12V	B	12	7.0~13.2	3.10	8000	4.95	174.98	46.03	1.81	66.5	250
AGE09238B24V	B	24	14.0~26.4	1.45	8000	4.95	174.98	46.03	1.81	66.5	250

*Bearing system B: Two Ball Bearing F: Fluid Bearing S: Sleeve Bearing

